

SEALCOAT

High Quality Primer / Sealer

DESCRIPTION & USES

- **SEALCOAT** is acrylic co-polymer water based primer cum sealer.
- **SEALCOAT** is suitable for interior and exterior use.
- Can be applied on concrete, cement surfaces and gypsum plasters, brick works, renderings, putties and stucco.
- **SEALCOAT** helps in penetrating porous surfaces to provide good bonding. Therefore it also helps to increase the spreading rate of finish products.
- Apply **SEALCOAT** as primer/sealer coat over prepared surface as well as over smoothed putty for the best results.
- It is water based environment friendly product.

PROPERTIES

Finish	Clear – Glossy, White – Low sheen
Color	Available in White and Clear
Density at 25°C	Approx 1.00 kg/ lit. (Clear) / 1.14 kg/ lit. (White)
Viscosity at 25°C	Approx 90 KU
% Solid Content by volume ASTM D 2697	18 ± 2
Diluent/Thinner	Water
Drying Time at 25°C and relative humidity 50%	<ul style="list-style-type: none"> • Touch Dry : 20-30 min. • Recoat : 4-5 hours. • Hard Dry : 24 hours.

INSTRUCTIONS FOR USE

- Surface must be clean, free from grease, dust, and other contaminants.
- Dilute: 1:1 – 1:2 with water, and use brush/roller for better penetration.
- On gypsum boards, apply **SEALCOAT** with only 50% dilution.

NOTE: For better results, complete removal of loosely adhered material is strongly recommended before application of **SEALCOAT**.

APPLICATION TOOLS

Brush - Roller - Spray Gun.

COVERAGE

15 - 25 m²/lit. per coat depending on dilution, porosity of substrate, application method and losses.

PACKAGING

Refer to company price list or contact local representative.

STORAGE & SHELF- LIFE

18 months in original tightly closed containers away from direct sunlight and excessive heat.

Refer safety data sheet before using the product.